

**247.3293**

**FLUSH MOUNTING APPLIANCE INLET**  
**32A 2P+E 6h 200-250V 60Hz 50Hz**  
**70X87MM Screw terminals**



\* Product image may be indicative



EN 60309-2/A1 (2007)  
EN 60309-1 (1999)  
EN 60309-2 (1999)  
EN 60309-1/A1 (2007)  
Low voltage direct. 2014/35/EU

**GENERAL CHARACTERISTICS**

Commercial Series	EUREKA Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Description	

The EUREKA Series flush mounting appliance inlet, engineered for robust electrical performance, is designed to operate at a rated voltage of 200-250V and a rated current of 32A, ensuring reliable power delivery. It features a 2P+E configuration with a 6h hour position, suitable for both 50Hz and 60Hz working frequencies. The inlet offers superior protection with an IP66/IP67 rating, safeguarding against dust and water ingress. Equipped with screw terminals, it ensures secure and efficient connections. Available in a 90° angled outlet type, this inlet is a dependable choice for demanding industrial environments.

Mounting version	FLUSH/SURFACE MOUNTING
------------------	------------------------

**TECHNICAL CHARACTERISTICS**

Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

**PHYSICAL CHARACTERISTICS**

Mounting version	FLUSH/SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK07
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	PG 16

**DIMENSIONAL CHARACTERISTICS**

Flange	70X87MM
--------	---------

**DOWNLOAD**

[Technical drawing \[PDF\]](#)  
[Technical drawing \[DWG\]](#)  
[Technical drawing \[STP\]](#)