



MiniPlug connection cable 1,5mm²

Item no: see below



230V ~ 50Hz CE



MiniPlug connection cable 1,5mm²

DEFA MiniPlug (A) is to be fitted into the specially developed MiniPlug inlet cable connector which is made to be discretely integrated in the front of modern streamlined vehicles. (Ref. DEFA MiniPlug inlet cable product sheets)

The DEFA Connection cables MiniPlug end (A), is also called DEFA EcoPlug.

Only use original DEFA MiniPlug connection cable together with DEFA MiniPlug inlet cable and connect the DEFA MiniPlug connection cable only to an earthed power socket. Fit and install parts according to the enclosed usage & installation guide.

Use

Connect the DEFA EcoPlug (A) to the DEFA MiniPlug inlet cable contact in the front of your vehicle. Make sure not to harm or damage the DEFA MiniPlug connection cable. Ensure not to damage the cable insulation by squeezing the cable under the hood or in the doorway. Keep the cap on the DEFA EcoPlug when the cable is not in use.

Maintenance

Disconnect the cable. Apply some silicon spray on the MiniPlug contact terminals before and after the season and ensure that either the cable or cap is damaged.

Technical specifications

Voltage [V]	250
Fuse [A]	16
Lenght [M]	2.5, 3.5, 5.0
MiniPlug [IP] IP rating	44
Testing & acceptance	EN 60309-1, EN 60309-2

Item no:

460920	Weight: 420g. (22ex x 2,5m pr. assembly box)
460933	Weight: 420g. (22ex x 2,5m pr. assembly box) (angled contact)
460938	Weight: 510gr. (22ex x 3,5m pr. assembly box)
460921	Weight: 695g. (12ex x 5,0m pr. assembly box)

Approvals

DEFA AS is conforming to the requirements ISO 9001, ISO 14001 and ISO 45001. In addition to this, our engine heaters and cables are conforming to the requirements of IATF 16949.



SCAN ME

defa.com