www.EUROPOWERGenerators.com

# EP18000TE

Article code: 950001803



**Europopower standard generating sets with air-cooled gasoline engines, 3000rpm, 50Hz, 4 stroke**

| | |
|---|---|
| **Generator:** | |
| kVA max.: | 17.5 |
| kVA cont.: | 16 |
| kVA: | 5.3kVA @ 1~230V 16kVA @ 3~400V |
| Amps cont.: | 23A @ 1~230V 23A @ 3~400V |
| Dimensions l x w x h: | 102x55x60cm |
| Dry weight: | 163kg |
| Weight incl. oil (+ coolant if water-cooled), excl. fuel: | 165kg |
| Weight incl. oil (+ coolant if water-cooled) + fuel: | 180kg |
| **Engine:** | |
| **Brand/Type:** | **Honda iGX800 RH-VXE4** |
| HP max.: | 22 |
| Power: | 16kW max. (3000rpm), 2-cylinder Gasoline, Air-cooled |
| Displacement: | 779cm³ |
| Consumption @75% load: | 5.6 litres/hour |
| Tank: | 20 litres |
| Autonomy @75% load: | 3.6 hours |
| Noise level: | 76dB(A)@7m (*) |
| EU Emission norm: | Stage V |
| Battery voltage: | 12V |
| CO2 emission: | 0 g/kWh |
| **Alternator:** | |
| **Brand/Type** | **Sincro FT2MGS** - with brushes |
| Nominal voltage: | 3~400V and 1~230V |
| Frequency: | 50Hz |
| Protection degree: | IP23 |

www.EUROPOWERGenerators.com

Generators with * cannot be used outdoors in the EU. For applications of generating sets indoors, or if you want to integrate these generators in vehicles, please contact us.

**Version:**

- 1 socket 230V - 16A + 1 socket CEE 400V - 32A 5 p.
- ECO-Throttle (Automatic Idle System)
- Electric start, maintenance free battery included
- Electronic speed governor
- Frame
- High temperature security
- Hour counter
- Oil guard
- Thermal magnetic breaker

www.EUROPOWERGenerators.com

POWERED by HONDA

sincro®

Your EUROPOWER dealer

DYNASTART