

## EP6500TE-25

Artikel code: 950000659



**Europower semi-geluidsgedempte long run stroomaggregaten met Honda luchtgekoelde benzinemotor, 3000tpm, 50Hz, 4-takt**

### Aggregaat:

|                                                                            |                                  |
|----------------------------------------------------------------------------|----------------------------------|
| kVA max.:                                                                  | 7                                |
| kVA cont.:                                                                 | 6.5                              |
| kVA:                                                                       | 4kVA @ 1~230V    6.5kVA @ 3~400V |
| Ampère (continu):                                                          | 17A @ 1~230V    9.4A @ 3~400V    |
| Afmetingen (l x b x h):                                                    | 80x58x63cm                       |
| Gewicht incl. olie (+ koelvloeistof indien watergekoeld), excl. brandstof: | 110kg                            |
| Gewicht incl. olie (+ koelvloeistof indien watergekoeld) + brandstof:      | 129kg                            |

### Motor:

#### Merk/Type:

**Honda GX390 RT2-VSD4**

|                      |                                                           |
|----------------------|-----------------------------------------------------------|
| pk max.:             | 11.1                                                      |
| Vermogen:            | 8.2kW max. (3000tpm), 1-cilinder<br>Benzine, Luchtgekoeld |
| Cilinderinhoud:      | 389cm <sup>3</sup>                                        |
| Verbruik @75% last:  | 2.4 liter/uur                                             |
| Tank:                | 25 liter                                                  |
| Autonomie @75% last: | 10.4 uur                                                  |
| Geluidsniveau:       | 71dB(A)@7m = Lwa 96                                       |
| EU-Emissie norm:     | Stage V                                                   |
| Batterij spanning:   | 12V                                                       |
| CO2 emissie:         | 0 g/kWh                                                   |

### Alternator:

#### Merk/Type

**Sincro ET2MCF - met borstels**

|                    |                  |
|--------------------|------------------|
| Nominale spanning: | 3~400V en 1~230V |
| Frequentie:        | 50Hz             |
| Beschermingsgraad: | IP23             |

**Versie:**

- 1 stopcontact 230V - 16A + 1 stopcontact CEE 400V - 16A 5 p.
- Automatische choke (voor temperaturen >0°C)
- Elektrische start, incl. onderhoudsvrije accu
- Frame
- Mechanische brandstofniveaumeter
- Olieniveaubeveiliging
- Repeteerstarter
- Thermo-magnetische beveiliging
- Urenteller
- Voltmeter



**DYNASTART**