

Warranty

- 5 years Manufacturer Warranty
- Warranty on Electrical Performance: 8 years power output

Manufacturing

- Original cell sorting system ensures the best of cells' electric match
- EL-Testing before packing
- Comprehensive module power testing, 100% positive output tolerance guaranteed

Performance

- High module conversion efficiency
- High-quality cells and partial-cell design lower series resistance and reduce power degradation
- Optimized performance under low light conditions and with the integrated bypass-diodes, the panel can still work when partially shaded
- IP67 rated junction box, reliable cables improves the stability



SZ-55-M

Mechanical Data Standard Test Conditions AM=1.5, E=1000W/m2, TC=25°C	
Nominal Power	55W
Cell Type	Monocrystalline
Cell Efficiency	22%
Maximum Power Current (Impp)	2.97A
Maximum Power Voltage (Vmpp)	18.56V
Open-circuit Voltage (Voc)	21.76V
Short-circuit Current (Isc)	3.15A
Maximum System Voltage	500V
Output Tolerance	0~+3%
Module Structure	Aluminum Frame / Glass / EVA / Backsheet
Junction box rating	≥IP67
Diode	- 11 01
Working Temperature	-40°C~+80°C
Packaging	
Module Dimensions	790*395*30mm
Module Weight	2.85kg
Package	Single Package
Pieces per Pallet	Free
Gross Weight per Pallet	Free
Pallet Dimensions	Free



